


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G02B 6/42	A1	(11) International Publication Number: WO 98/35253 (43) International Publication Date: 13 August 1998 (13.08.98)
(21) International Application Number: PCT/GB98/00382 (22) International Filing Date: 6 February 1998 (06.02.98) (30) Priority Data: 9702559.7 7 February 1997 (07.02.97) GB (71) Applicant: BOOKHAM TECHNOLOGY LIMITED [GB/GB]; 90 Milton Park, Abingdon, Oxon OX14 4RY (GB). (72) Inventors: HARPIN, Arnold, Peter, Roscoe; 58 Stratford Street, Oxford OX4 1SW (GB). RICKMAN, Andrew, George; St. Katherines Lodge, Savernake Forest, Marl- borough, Wilts SN8 3BG (GB). MORRIS, Robin, Jeremy, Richard; 43 Henley Street, Oxford OX4 1ES (GB). GOR- TON, Stephen; 20 Winterbourne Road, Abingdon, Oxon OX14 1AJ (GB). ASGHARI, Mehdi; 53 Godolphin Close, Freshbrook, Swindon Wilts SN5 8RN (GB). (74) Agent: S.G. UNWIN & CO.; Brookfurlong Farmhouse, Islip, Oxford OX5 2TJ (GB).		(81) Designated States: AU, CA, CN, IL, JP, KR, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

(54) Title: DEVICE FOR RE-DIRECTING LIGHT FROM OPTICAL WAVEGUIDE**(57) Abstract**

The device is formed on a silicon-on-insulator chip (which comprises a layer of silicon (1) separated from a substrate (3) by an insulator layer (2)) and comprises an integrated waveguide (4) formed in the silicon layer (1) and a reflective facet (6) formed in a recess in the silicon layer (1). The facet (6) is positioned to redirect light in a desired direction. The waveguide (4) and facet (6) are both formed in the silicon layer (1) so their positions can be defined by the same lithographic steps so they are automatically aligned with each other.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

DEVICE FOR RE-DIRECTING LIGHT FROM OPTICAL WAVEGUIDE

TECHNICAL FIELD

This invention relates to a device for re-directing light from an optical waveguide on a silicon-on-insulator chip.

BACKGROUND ART

In integrated optical circuits, there is often a requirement to re-direct light from an optical waveguide, e.g. from a waveguide formed on the chip to a receiver, such as a photodiode, mounted on the chip. A variety of ways of achieving this have been proposed in a variety of types of integrated optical circuits, e.g. by positioning a photodiode within a recess formed in the chip so it receives light emerging from a waveguide on the chip. Many of the known arrangements are, however, difficult to fabricate accurately and inexpensively due to the requirement of ensuring accurate positioning and alignment of the various components concerned.

This invention aims to provide a device formed on a silicon-on-insulator chip and which employs features of such a chip and of waveguides formed thereon to assist in the alignment of the components of the device.

DISCLOSURE OF INVENTION

According to the present invention, there is provided a device for re-directing light from an optical waveguide on a silicon-on-insulator chip which comprises a layer of silicon separated from a substrate by an insulator layer, the device comprising an integrated waveguide formed in the silicon layer and a reflective facet formed in a recess in the silicon layer, the facet being positioned to receive light from the waveguide and angled so as to re-direct the light in a desired direction, the waveguide and facet both being formed in the silicon layer so their locations can be defined by the same lithographic step.

Preferred and optional features of the invention will be apparent from the following description and from the subsidiary claims of the specification.

BRIEF DESCRIPTION OF DRAWINGS

The invention will now be further described, merely by way of example, with reference to the accompanying drawings, in which

Figure 1 shows a schematic, perspective view of an integrated optical circuit which includes at least one photodiode for receiving light transmitted along a waveguide formed on the device;

Figure 2 is a schematic cross-sectional view through a silicon-on-insulator chip showing an embodiment of a device according to the invention for re-directing light from a waveguide on the chip to a photodiode; and

Figures 3A to 3D show schematic plan views of various embodiments of the device.

BEST MODE OF CARRYING OUT THE INVENTION

As indicated above, this invention relates to devices formed on silicon-on-insulator wafers which are readily commercially available. The chip comprises a layer of silicon separated from a silicon substrate by a layer of silicon dioxide. The thickness of the upper layer of silicon is typically increased to the required size by epitaxial growth.

Integrated optical waveguides in the form of ribs may be formed in the upper silicon layer. Methods of manufacturing such waveguides are described in the paper "Low loss single mode optical waveguides with large cross-section in silicon-on-insulator" by J. Schmidtchen et al, Electronic Letters, 27,p1486,1991.

Figure 2 shows the silicon layer 1, the silicon dioxide layer 2 and the silicon substrate 3. A rib waveguide 4 is formed in the silicon layer 1 which is typically around 5 or 10 microns in thickness. The waveguide 4 terminates at a facet 4A in a recess 5 formed in the silicon layer 1. On the opposite side of the recess 5, a facet 6 is formed on a side surface of the silicon layer 1. The facet 6 is coated with aluminium (or other optically reflective coating) and is angled at 54.7 degrees to the axis of the waveguide 4. Light emerging from the waveguide facet 4A thus falls on the facet 6 and is reflected so as to be re-directed in a direction substantially perpendicular to the plane of the chip. With a facet angled at 54.7 degrees to the axis of the waveguide, the light is reflected in a direction lying 19.4 degrees to the vertical.

The facet 6 may be formed at an angle determined by a crystallographic plane of the silicon or may be formed at other angles, e.g. by dry etching.

In another embodiment (not shown), the position of the silicon layer 1 in which the facet 6 is formed may have a greater thickness than the portion of the silicon layer 1 in which the waveguide 4 is formed. The facet 6 may thus be of larger size so a larger proportion of light diverging from the end of the waveguide 4 is intercepted by the facet and reflected in the desired direction.

An InGaAs photodiode 7 is soldered (7B) on the chip over the recess 5 by standard eutectic die attach techniques so that its active region 7A is located in alignment with the light reflected by the angled facet 6.

Electrical connection is made to the photodiode 7 by means of a wire bond 7C which connected with conductor tracks or circuitry provided on the upper surface of the chip.

The arrangement described above has the benefit of being simple, yet easy to fabricate. Alignment of the facet 6 with the waveguide 4 is achieved

automatically firstly because the facet is formed in the same silicon layer in which the waveguide is formed so is automatically aligned in the vertical direction and, secondly, the location of the recess 5 and facet can be defined by the same photolithographic step used to define the location of the waveguide, so they are automatically aligned in the lateral direction.

As will be appreciated from the above, the facet is monolithically formed from the same silicon-on-insulator chip as the silicon waveguides and, like the waveguides, is formed in the epitaxial layer 1 of silicon rather than in the silicon substrate 3. The recess 5 and facet 6 are micro-machined by means of appropriate masking and etching steps and may, for instance, be etched using caesium hydroxide which preferentially etches the silicon layer 1. The silicon dioxide layer 2 acts as a natural etch stop during this process.

By this means the facet 6 can be formed directly opposite the end of the waveguide 4 and the distance between the waveguide facet 4A and the reflective facet 6 can be kept to a minimum, e.g. to less than 15 microns, and preferably less than 10 microns. This helps reduce losses due to the divergence of the light emitted from the waveguide facet 4A to a minimum.

The active region 7A of the photodiode 7 typically has a diameter of around 125 microns so needs to be located on the silicon chip over the recess 5 with a positional tolerance of around ± 50 microns.

It will be appreciated that a similar arrangement may be used to direct light from a waveguide to other forms of light receivers mounted on the chip or to direct light from a light source, e.g. a laser or light emitting diode, mounted on the chip into a waveguide formed thereon. A vertical cavity surface emitting laser (not shown) may, for instance, be mounted over the recess 5 so as to direct light onto the facet 6.

The facet 6 may be formed at other angles so as to direct light in a desired direction. Light would typically be directed out of the plane of the chip but may also be directed to a device or another waveguide on the chip.

In addition, it may be desirable to angle the facet 6 about an axis perpendicular to the plane of the chip to reduce problems due to back reflection, particularly from areas at the edge of the facet which can back-reflect into the waveguide 4 if the edges of the facet 6 lie perpendicular to the waveguide axis. A similar result can be achieved by forming the waveguide at an angle and/or providing an angled facet 4A on the end of the waveguide 4.

These possibilities are illustrated in Figures 3A to 3D which each show plan views of the chip. Figure 3A shows a plan view of the arrangement illustrated in Figure 2 which can give rise to back reflections if vertical surfaces exist on the facet 6. In figure 4A the light is shown being re-directed out of the plane of the chip in a direction normal to the chip. Figure 3B shows an arrangement in which the facet 6 has been further tilted about an axis perpendicular to the chip compared to Figure 3A. Figure 3C shows an arrangement in which the waveguide 4 is formed at an angle across the chip compared to the arrangement of Figure 3A and Figure 3D shows an arrangement in which the waveguide facet 4A of the waveguide 4 is angled so light emerging therefrom is refracted away from the axis of the waveguide. In each case, the arrangement causes the light to be re-directed out of the plane of the chip but at an angle to the normal thereof. This may require the position of the photodiode 7 over the recess 5 to be adjusted slightly to ensure it receives the re-directed light.

Figure 1 shows a perspective view of an integrated optical circuit, in this case a transceiver, formed on a silicon-on-insulator chip 8. Two photodiodes 9 and a laser 10 are mounted on the chip 8. Light is transmitted to the chip 8 by an optical fibre 11 and rib waveguides 12 are provided on the chip 8 for transmitting light to the various components. Figure 2 described above

illustrates the manner in which light is directed from a rib waveguide 12 to one of the photodiodes 9.

CLAIMS

1. A device for re-directing light from an optical waveguide on a silicon-on-insulator chip which comprises a layer of silicon separated from a substrate by an insulator layer, the device comprising an integrated waveguide formed in the silicon layer and a reflective facet formed in a recess in the silicon layer, the facet being positioned to receive light from the waveguide and angled so as to re-direct the light in a desired direction, the waveguide and facet both being formed in the silicon layer so their locations can be defined by the same lithographic step.
2. A device as claimed in Claim 1 in which the facet is angled to direct light out of the plane of the chip.
3. A device as claimed in Claim 2 in which the facet is angled to direct light in a direction substantially perpendicular to the plane of the chip.
4. A device as claimed in Claim 2 in which the facet is angled to direct light out of the plane of the chip at an angle to the normal of the chip.
5. A device as claimed in Claim 4 in which the facet is angled so its edges do not lie perpendicular to light received from the waveguide.
6. A device as claimed in any preceding claim arranged to direct light received from the optical fibre to a photodiode mounted on the chip.
7. A device as claimed in Claim 6 in which the photodiode is mounted over the recess in which the facet is formed.
8. A device as claimed in any of Claims 1 to 5 in which a laser or light emitting diode is mounted over the recess in which the facet is formed.

9. A device as claimed in any preceding claim in which the distance between the end of the waveguide and the facet is less than 15 microns, and preferably less than 10 microns.
10. A device for re-directing light from an optical waveguide on a silicon-on-insulator chip substantially as hereinbefore described with reference to Figures 2 and 3 of the accompanying drawings.
11. An integrated optical circuit including a device as claimed in any of Claims 1 to 10.
12. An integrated optical circuit substantially as hereinbefore described with reference to Figures 2 and 3 of the accompanying drawings.

1/2




Fig. 1








Fig. 2

2/2



A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G02B6/42

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 331 338 A (AMERICAN TELEPHONE & TELEGRAPH) 6 September 1989 see abstract; figures 1,2,6 see column 3, line 16 - column 4, line 52 ---	1-8,11
Y	US 5 263 111 A (NURSE JAMES ET AL) 16 November 1993 see abstract; figures 18-24,27 see column 13, line 21 - column 15, line 16 see column 10, line 48 - column 11, line 38 ---	1-5,11
Y	US 5 489 988 A (ACKLEY DONALD E ET AL) 6 February 1996 see abstract; figure 4 see column 4, line 28-51 --- -/--	1,4,6-8

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

28 May 1998

Date of mailing of the international search report

09/06/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Beaven, G

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 282 080 A (SCIFRES DONALD R ET AL) 25 January 1994 see abstract; figures 1,12-15 see column 7, line 65 - column 8, line 48 ---	1,4
Y	US 5 311 604 A (ROGNER ARND ET AL) 10 May 1994 see abstract; figure 3 see column 7, line 31-47 ---	1
Y	PATENT ABSTRACTS OF JAPAN vol. 012, no. 470 (P-798), 9 December 1988 & JP 63 191111 A (NIPPON TELEGR & TELEPH CORP), 8 August 1988, see abstract; figure 3 ---	1-3
Y	SCHUPPERT B ET AL: "INTEGRATED OPTICS IN SI AND SIGE-HETEROSTRUCTURES" PROCEEDINGS OF THE EUROPEAN CONFERENCE ON OPTICAL COMMUNICATION (EC INVITED PAPERS, BERLIN, SEPT. 27 - OCT. 1, 1992 BOUND AS ONE WITH VOLUMES 1 & 3, vol. VOL. 2, no. CONF. 18, 27 September 1992, INFORMATIONSTECHNISCHE GESELLSCHAFT IM VDE, pages 793-800, XP000559168 see page 795, line 23-35; figure 8 -----	1

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0331338 A	06-09-89	SG 154394 G	17-03-95
		US 4904036 A	27-02-90
		DE 68918133 D	20-10-94
		DE 68918133 T	12-01-95
		ES 2058498 T	01-11-94
		JP 2005611 C	11-01-96
		JP 2009187 A	12-01-90
		JP 7034495 B	12-04-95
		CA 1309157 A	20-10-92
		HK 191995 A	29-12-95
US 5263111 A	16-11-93	WO 9218888 A	29-10-92
US 5489988 A	06-02-96	NONE	
US 5282080 A	25-01-94	NONE	
US 5311604 A	10-05-94	DE 4207207 A	09-09-93
		DE 4217526 A	02-12-93
		DE 59306756 D	24-07-97
		EP 0560043 A	15-09-93
		FI 930989 A	08-09-93
		JP 6003545 A	14-01-94